

**ALEX**

.118"(3.0mm) Wire-to-Wire Crimp Terminal Housing

Specifications:

- Voltage rating: 250V AC(RMS) or DC
- Dielectric Strength: 1500V AC/minute
- Current rating:


Wire size	# 20	# 22	# 24	# 26	# 28	# 30
Ampere	5 A	5 A	4 A	3 A	2 A	1 A

- Insulation resistance: 1000M Ω Min.
- Contact resistance: 10m Ω Max.
- Temperature rise: 30°C Max.
(carry rated current load)

- UL file No.: E114003
- CSA file No.: LR86545

3030T Female Crimp Terminal

- Material: Phosphor bronze
- Finished: Tin-plated or Gold flash
- Used in ALEX 3025-N, 3025-xxS housings
- Wire range: AWG #20 ~ #30
- Thickness: 0.2mm



Ordering Information

Part No.	Finished	Wire size
3030T1 3030T1-L	Tin-plated	#26 ~ #30 AWG
3030T2 3030T2-L		#20 ~ #24 AWG
3030T1-xGC 3030T1-L-xGC	Gold flash in contact area. Others: Tin-plated	#26 ~ #30 AWG
3030T2-xGC 3030T2-L-xGC		#20 ~ #24 AWG
3030T1-xGF 3030T1-L-xGF	Gold flash	#26 ~ #30 AWG
3030T2-xGF 3030T2-L-xGF		#20 ~ #24 AWG

&& x means the u" of gold flash.

3025-N Series Dual Row Receptacle Housing

- Available in 2 thru 24 circuits
- Material: UL 94V-0 nylon 66
- Standard color: Black
- Accepts ALEX 3030Tx, 3030Tx-L terminals
- Mates with ALEX 3020-N housing
- Mates with ALEX 3045-N, 3046-N, 3047-xx, 3048-xx headers


Dimensional Information (mm)

Circuits	Dim. A	Dim. B
N	3 x (N / 2 - 1)	A + 4.25

&& N = 2~24

Ordering Information

Circuits	Description
02~10	Accepts ALEX 3030Tx, 3030Tx-L
12~24	Accepts ALEX 3030Tx-L



**ALEX**

.118"(3.0mm) Wire-to-Wire Crimp Terminal Housing

Specifications:


- Voltage rating: 250V AC(RMS) or DC
- Dielectric Strength: 1500V AC/minute
- Current rating:
- Insulation resistance: 1000M Ω Min.
- Contact resistance: 10m Ω Max.
- Temperature rise: 30°C Max.
(carry rated current load)

Wire size	# 20	# 22	# 24	# 26	# 28	# 30
Ampere	5 A	5 A	4 A	3 A	2 A	1 A

- UL file No.: E114003
- CSA file No.: LR86545

3031T Male Crimp Terminal


- Material: Phosphor bronze
- Finished: Tin-plated or Gold flash
- Used in ALEX 3020-N, 3020-xxS housings
- Wire range: AWG #20 ~ #30
- Thickness: 0.2mm



inches
mm

Ordering Information


Part No.	Finished	Wire size
3031T1	Tin-plated	#26 ~ #30 AWG
3031T2		#20 ~ #24 AWG
3031T1-xGC	Gold flash in contact area.	#26 ~ #30 AWG
3031T2-xGC	Others: Tin-plated	#20 ~ #24 AWG
3031T1-xGF	Gold flash	#26 ~ #30 AWG
3031T2-xGF		#20 ~ #24 AWG



& x means the u" of gold flash.

3020-N Series Dual Row Receptacle Housing

- Available in 2 thru 24 circuits
- Material: UL 94V-0 nylon 66
- Standard color: Black
- Accepts ALEX 3031T terminal
- Mates with ALEX 3025-N housing
- Recommended panel thickness: 1.57mm



Ordering Information

Part No.	Feature
3020-xxE	With mounting ears
3020-xx	Without mounting ears

Dimensional Information (mm)

Circuits	Dim. A	Dim. B	Dim. C	Dim. D
N	3 x (N / 2 - 1)	A + 4	A + 4.22	A + 7.88

& N = 2 ~ 24

**ALEX**

.118"(3.0mm) Wire-to-Wire Crimp Terminal Housing

Specifications:

- Voltage rating: 250V AC(RMS) or DC
- Dielectric Strength: 1500V AC/minute
- Current rating:


Wire size	# 20	# 22	# 24	# 26	# 28	# 30
Ampere	5 A	5 A	4 A	3 A	2 A	1 A

- Insulation resistance: 1000M Ω min.
- Contact resistance: 10m Ω max.
- Temperature rise: 30 °C max.
(carry rated current load)

- UL file No.: E114003
- CSA file No.: LR86545


3025-xxS Series Single Row Receptacle Housing

- Available in 2 thru 12 circuits
- Material: UL 94V-0
- Standard color: Black
- Accepts ALEX 3030Tx, 3030Tx-L terminals
- Mates with ALEX 3020-xxS series housing
- Mates with ALEX 3045-xxS, 3046-xxS, 3047-xxS, 3048-xxS headers



3020-xxS Series Single Row Plug Housing

- Available in 2 thru 12 circuits
- Material: UL 94V-0
- Standard color: Black
- Accepts ALEX 3031T series terminals
- Mates with ALEX 3025-xxS series housing
- Recommended panel thickness: 1.57mm



Ordering Information

Part No.	Feature
3020-xxES	With mounting ears
3020-xxS	Without mounting ears

Dimensional Information - in (mm)

Circuits	Dim. A	Dim. B	Dim. C	Dim. D	Circuits	Dim. A	Dim. B	Dim. C	Dim. D
2	0.118 (3.0)	0.276 (7.0)	0.284 (7.21)	0.429 (10.90)	8	0.827 (21.0)	0.984 (25.0)	0.992 (25.20)	1.137 (28.88)
3	0.236 (6.0)	0.394 (10.0)	0.402 (10.21)	0.547 (13.89)	9	0.945 (24.0)	1.102 (28.0)	1.110 (28.20)	1.255 (31.88)
4	0.354 (9.0)	0.512 (13.0)	0.520 (13.21)	0.665 (16.89)	10	1.063 (27.0)	1.220 (31.0)	1.229 (31.22)	1.373 (34.87)
5	0.472 (12.0)	0.630 (16.0)	0.638 (16.21)	0.783 (19.89)	11	1.181 (30.0)	1.339 (34.0)	1.347 (34.22)	1.491 (37.87)
6	0.591 (15.0)	0.748 (19.0)	0.756 (19.21)	0.901 (22.89)	12	1.299 (33.0)	1.457 (37.0)	1.465 (37.22)	1.609 (40.87)
7	0.709 (18.0)	0.866 (22.0)	0.874 (22.20)	1.019 (25.88)					